

VITA CABLES — Veehi Engineering Private Limited

Your Power, Our Cables & Wires | IEC 61931| IEC 62930|
IEC|60811 Compliant

PRICE LIST | Valid From: 01/05/2026 To: 31/07/2026 (All prices in ₹ per metre, exclusive of GST)

SOLAR PV CABLE

Size (sq mm)	DC Resistance @ 20 degree C.	Insulation Thickness (mm)	Sheath Thickness (mm)	Overall Dia (mm)	Current rating	Price Per meter.
1.5 sq mm	13.7	0.6	0.7	4.4	22	51
2.5 sq mm	8.71	0.7	0.8	5.2	30	82
4.0 sq mm	5.09	0.7	0.8	5.8	42	104
6.0 sq mm	3.39	0.8	1	6.2	52	182
10.0 sq mm	1.95	1	1	7.2	76	302
16.0 sq mm	1.24	1	1.2	8.4	96	483

★ Flexible fine-stranded tinned copper conductor. Suitable for Solar Panels and Pumps.

★ Prices per metre excluding GST @18%. Custom lengths & colours available on request. Min order: 100 mtrs.

For orders & enquiries contact: VITA Cables — Veehi Engineering Private Limited |
Phone: +91 9898097945 | Email: sales@vitacable.com | Website: www.vitacable.com